



PO BOX 1429
 3811 NORTH BRIDGE ST
 BRADY, TEXAS 76825
 Phone 325-597-2911
 Fax: 325-597-0781
 800-803-0183

DESCRIPTION:

MODEL:

CAPACITY @ 60 MPH,96 KPH

WIDTH

LENGTH

FRAME CONSTRUCTION

CROSSMEMBERS

50 TON DETACHABLE GOOSENECK 3 AXLE

LCO-LBDT-50-T-3

50 TONS 45372 kg

8.5 ft 2591 mm

54.5 ft 16612 mm

FABRICATED IBEAMS OUT OF T-1 FLANGES AND DOMEX WEBS
 24" SPACING

GOOSENECK

SWING RADIUS

FIFTH WHEEL HT

MECHANICAL-DETACHABLE- NARROW

90 in 2286 mm

54 in 1372 mm

DECK

LENGTH

WIDTH

LOAD HT

CONCENTRATED LOAD

FLOORING

"D" RINGS

40.0 ft 12192 mm

8.5 ft 2591 mm

40 in 1016 mm

50 TONS 45372 KG

APITONG OR =HARD WOOD FLOORING - 2" NOMINAL
 STD 6 PER SIDE

SUSPENSION AREA

AXLES

BRAKES

SUSPENSION

TIRES

WHEELS, STEEL

BOLSTERS

3 AXLES

25000 LB CAPACITY 5" DIA AXLES

16 1/2" X 7" AIR -W/ AUTO SLACKS & PARKING BRAKES

THREE AXLE AIR RIDE

255/70R22.5 OEM

8.25 X 22.5 HP 10 HOLE 11 1/4" BC

STD. FLAT BETWEEN TIRES

TAIL ROLLER

BUMPER

8 5/8" H D W/ 22317 BNGS, TWO SETS / OVERLOADS

HEAVY DUTY OIL FIELD

BRAKE SYSTEM

TWO LINE NON ABS

ELECTRICAL

LIGHTS

HARNESS

12 VOLT US

LED STANDARD

MODULAR, WITH 7-WAY CONNECTOR

PAINT PREPARATION

FINISH

AVAILABLE COLORS

APPROX EMPTY WEIGHT

SHOT BLAST

EPOXY PRIMER - POLYURETHANE TOP COAT

BLACK, CAT YELLOW, OR RED

26,600 lbs 12069 kg

AVAILABLE OPTIONS

GSNK OPTIONS

120" /3 KING PIN SETTINGS
INVERTED FIFTH WHEEL

TRAILER WIDTH OPTION

9' WIDE, 2745 mm
10' WIDE, 3050 mm

COVERED WHEEL WELLS

AIR LIFT AXLES

OUTRIGGERS

SUPSPENSION

ABS BRAKES

POP UP DECK ROLLERS